



Wall mounted units

Total comfort at home



Creating the perfect climate is what Daikin units are all about. These wall mounted units offer pleasant comfort for less energy use.

FTXB-C + RXB-C



Efficiency data		FTXB + RXB		*25C + 25C	*35C + 35C	*50C + 50C	*60C + 60C
Cooling capacity	Min./Nom./Max.	kW		1.3/2.5/3.0	1.3/3.3/3.8	-/5.48/-	-/6.23/-
Heating capacity	Min./Nom./Max.	kW		1.3/2.8/4.0	1.3/3.5/4.8	-/5.6/-	-/6.4/-
Power input	Cooling	Nom.	kW	0.77	0.99	1.71	1.93
	Heating	Nom.	kW	0.69	0.93	1.49	1.77
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A+			
		Pdesign	kW	2.50	3.30	5.48	6.23
		SEER		6.00	6.05	5.93	6.09
		Annual energy consumption	kWh	146	191	323	358
	Heating (Average climate)	Energy label		A+			
		Pdesign	kW	2.40	2.80	3.64	3.80
		SCOP		4.01	4.06	4.27	4.06
		Annual energy consumption	kWh	838	966	1,193	1,310

Indoor unit		FTXB		*25C	*35C	*50C	*60C
Dimensions	Unit	HeightxWidthxDepth	mm	316x870x310		386x1136x314	
Weight	Unit		kg	8		14	
Sound power level	Cooling		dB(A)	55	58	55	61
	Heating		dB(A)	55	58	55	61

Outdoor unit		RXB		*25C	*35C	*50C	*60C
Dimensions	Unit	HeightxWidthxDepth	mm	616x788x359		793x990x415	
Weight	Unit		kg	27	29	49	
Sound power level	Cooling		dB(A)	60	62	64	65
	Heating		dB(A)	60	62	64	65
Operation range	Cooling	Ambient	Min.-Max.	°CDB ---			
	Heating	Ambient	Min.-Max.	°CWB ---			
Refrigerant	Type/GWP	R-410A/1,975					

*Note: blue cells contain preliminary data