

# Wall mounted unit

FTXS-K/FTXS-G



2 area intelligent eye



Energy saving during standby mode



Whisper quiet



Online controller via app



VRV for residential application

Discreet, modern design for optimal efficiency and comfort thanks to 2 area intelligent eye

- › Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!
- › Ideal for installation in bedrooms (smaller capacity range) and larger or irregularly shaped living areas (larger capacity range)
- › 2-area intelligent eye: air flow is sent to a zone other than where the person is located at that moment; if no people are detected, the unit will automatically switch over to the energy-efficient setting. (larger capacity area)

- › Online controller (optional): control your indoor from any location with an app, via your local network or internet and keep an overview on your energy consumption
- › 3-D air flow combines vertical and horizontal auto swing to circulate a stream of warm or cool air right to the corners of even large spaces (50,60,71 class only)

# FTXS-K/FTXS-G + RXS-L(3)/ RXS-F8



Indoor unit		FTXS	20K	25K	35K	42K	50K	60G	71G	
Casing	Colour		White							
Dimensions	Unit	HeightxWidthxDepth	289x780x215		298x900x215			290x1,050x250		
Sound power level	Cooling	dBA	58		59		60		63	
	Heating	dBA	58		59		60		62	
Sound pressure level	Cooling	High/Low/Silent operation	dBA	40/24/19	41/25/19	45/29/19	45/33/21	46/34/23	45/36/33	46/37/34
	Heating	High/Low/Silent operation	dBA	40/27/19	41/27/19	45/29/19	45/33/22	47/34/24	44/35/32	46/37/34
Control systems	Infrared remote control		ARC466A6		ARC466A9			ARC452A3		


EER/COP according to Eurovent 2012, for use outside EU only

Efficiency data		FTXS + RXS	20K + 20L3	25K + 25L3	35K + 35L3	42K + 42L	50K + 50L	60G + 60L	71G + 71F8		
Cooling capacity	Min./Nom./Max.	kW	-/2.00/-	-/2.5/-	1.4/3.5/4.0	1.7/4.20/5.0	1.7/5.00/5.3	1.7/6.0/6.7	2.3/7.10/8.5		
Heating capacity	Min./Nom./Max.	kW	1.3/2.5/4.3	1.3/2.8/4.7	1.4/4.00/5.2	1.7/5.40/6.0	1.7/5.80/6.5	1.7/7.0/8.0	2.3/8.20/10.2		
Power input	Cooling	Min./Nom./Max.	kW	0.320/0.455/0.760	0.320/0.593/1.000	0.350/0.860/1.190	0.320/1.253/2.330	0.350/1.506/1.810	0.440/1.990/2.400	0.570/2.350/3.200	
	Heating	Min./Nom./Max.	kW	0.310/0.530/1.120	0.310/0.600/1.410	0.340/0.840/1.460	0.400/1.310/1.980	0.300/1.450/2.000	0.400/2.040/2.810	0.520/2.550/3.820	
Seasonal efficiency (according to EN14825)	Cooling	Energy efficiency class	A++								
		Pdesign	kW	2.00	2.50	3.50	4.20	5.00	6.00	7.10	
	SEER		7.40	7.90	7.47	6.80		5.58	5.28		
	Annual energy consumption	kWh	95	111	164	216	257	376	471		
	Heating (Average climate)	Energy efficiency class	A+								
Nominal efficiency	Cooling	Pdesign	kW	2.30	2.50	3.60	4.00	4.60	4.80	6.20	
		SCOP/A		4.77	4.78	4.85	4.20		3.89	3.81	
	Annual energy consumption	kWh	675	732	1,039	1,334	1,535	1,728	2,276		
	EER		4.39	4.21	3.89	3.35	3.32	3.02			
	COP		4.72	4.67	4.76	4.12	4.00	3.43	3.22		
Annual energy consumption	Cooling	kWh	228	297	450	627	753	995	1,175		
	Heating		A							B	
Energy labeling	Direct		A							B	
Energy labeling	Heating		A							B	

Outdoor unit		RXS	20L3	25L3	35L3	42L	50L	60L	71F8	
Dimensions	Unit	HeightxWidthxDepth	550x765x285				735x825x300		770x900x320	
Sound power level	Cooling	dBA	59		61		62		65	
	Heating	dBA	58	59	61		62		66	
Sound pressure level	Cooling	High/Low/Silent operation	dBA	46/-/43	48/-/44		48/44/-	49/46/-	52/-/49	
	Heating	High/Low/Silent operation	dBA	47/-/44	48/-/45		48/45/-	49/46/-	52/-/49	
Operation range	Cooling	Ambient	Min.-Max.	-10~46						
	Heating	Ambient	Min.-Max.	-15~18						
Refrigerant	Type/Charge/GWP	kg/TCO <sub>eq</sub>	R-410A/1.0/2.1/2,087.5	R-410A/1.2/2.5/2,087.5	R-410A/1.3/2.7/2,087.5	R-410A/1.7/3.5/2,087.5	R-410A/1.5/3.1/2,087.5	R-410A/2.3/4.8/2,087.5		
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240			1~/50/220-230-240		1~/50/220-240		

Contains fluorinated greenhouse gases

**Daikin Europe N.V.** Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · [www.daikin.eu](http://www.daikin.eu) · BE 0412 120 336 · RPR Oostende (Responsible Editor)



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: [www.eurovent-certification.com](http://www.eurovent-certification.com) or using: [www.certiflash.com](http://www.certiflash.com)

ECPEN16-023

02/17



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.